



CABEÇOTE FRESADOR R-12

Milling Head R-12

MILLING HEADS

 MADE IN BRAZIL



12-SPEED milling head with up to 1,100 rpm and ISO 40/50 spindle for precision industrial machining. 5.0 or 8.0 hp motor options



CABEÇOTE FRESADOR R-12

MILLING HEAD R-12



Technical Specifications

INFORMATION

Rotation speeds	12
Tool holder shaft rotations	3.35 - 4.72 - 7.28 - 10.04 - 13.78 - 21.65 rpm (4.9 hp)
	6.30 - 9.45 - 14.57 - 20.08 - 27.56 - 43.31 rpm (7.9 hp)
Maximum lateral inclination - left / right - manual	45° / 45°
Maximum spindle shaft stroke - manual	2.36 in
Tool holder shaft cone	ISO 40 or ISO 50
Electric motor - power	4.9 / 7.9 hp
Normal installed electrical voltage	220 volts - 60hz - 3 phases
Housing dimensions (length x width x height)	16.93 x 21.06 x 12.20 in
Rotation transmission	Via steel gears with tempered and ground teeth and with automatic lubrication via pump
Automatic internal lubrication pump	Included
Prismatic base and spindle nut for adapting the head to the machine crossbeam	Included
Spindle for transverse movement of the milling head on the crossbeam	Optional
Sketch or drawing of the crossbeam for adapting the milling head to the machine where it will be installed	Required and at buyer's expense
Sub-head adaptable to the tool holder shaft	Optional
Rotation speeds	50% of original rotations

Specifications subject to change without notice. Some capacities listed may require optional accessories. Confirm exact dimensions during quotation.