



MACHINE INDUSTRY
CHINELATTO

TECHNICAL CATALOG
Since 1962 — Limeira (SP) - Brazil

CABEÇOTE FRESADOR R-4

Milling Head R-4

MILLING HEADS

 MADE IN BRAZIL



4-SPEED milling head with 5HP motor and 45° manual tilt capability. Delivers precision machining from 108-1260 RPM for industrial applications



CABEÇOTE FRESADOR R-4

MILLING HEAD R-4



Technical Specifications

INFORMATION

Rotation speeds	4
Tool holder spindle rotations	108 - 315 - 430 - 1260 rpm (4.9 hp)
Maximum lateral inclination - left / right - manual	45° / 45°
Maximum spindle axis stroke - manual	1.57 in
Tool holder spindle cone	ISO 40
Electric motor - power	4.9 hp
Standard electrical voltage installed	220 volts - 60hz - 3 phases
Housing dimensions (length x width x height)	11.22 x 12.80 x 10.24 in
Rotation transmission	Via steel gears with tempered and ground teeth and with automatic lubrication via pump.
Automatic internal lubrication pump	Included
Prismatic base and spindle nut for adapting the head to the machine crossbeam	Included
Spindle for transverse movement of the milling head on the crossbeam	Optional
Sketch or drawing of the crossbeam for adapting the milling head to the machine where it will be installed	Necessary and at the buyer's expense.
Sub-head adaptable to the tool holder spindle	Optional
Rotation speeds	50% of original rotations

Specifications subject to change without notice. Some capacities listed may require optional accessories. Confirm exact dimensions during quotation.